

## Product Specification Sheet

### Cylinder Wall Brackets

Part #'s G-100, G-200, G-300 & 401

- **Structure**
  - 11 Gauge hot rolled steel
  - Epoxy powder painted ASA 61 Gray
  - Edges protected with polypropylene sealed steel reinforced edge molding
  - Punched and formed
- **Dimensional**
  - 8.0, 23.75, & 35.75 inch wide by 4.25 inch high by 2.25 inch deep
  - 2.8, 8.0, & 10.7 lb. Each
  - Strap- 1.5 inch wide heavy gauge polypropylene with plated steel cinch style buckle rated assembly 1200 psi
  - Mounts to structural wall through rear of bracket
  - Formed access holes to fit with optional steel chain set
  - Chain set #1/0 plated steel twisted loop chain with plated steel quick-cinch bit snap -chain rated 525 lb. Stress tested
- **Design Criteria**
  - Holds one, two, three or four gas cylinders in the vertical position from 4.0 to 12.0 inch diameter
  - Designed to withstand repeated impacts from loading
  - Protected edges keep cylinders from damage, provide superior grip and security
  - All steel construction meets OSHA, UFC and seismic regulations for all 50 states when used with optional chain set Model G-105
  - Tested in service by gas manufacturers worldwide.

